

# DA West / LOADSTAR

PO Box 968, Friday Harbor, WA.98250 (360) DIESEL-1 \* 1(800)343-7351 \* (360)378-4182

WWW.DAWEST.COM
DIESEL EQUIPMENT SOLUTIONS

## DPL70-2MFC 2" CHEMICAL PUMP



#### **SPECIAL FEATURES:**

- Tig welded, 1" stainless steel, #304 square tube roll cage frame
- Variable speed governor allowing pump speed to match the job
- Long life oil-resistant internal parts with built in check valve
- Easy recoil starting with auto compression release and self fuel bleed Extra tough antivibration isolator, and nonskid feet
- All in all, a lightweight, rugged, diesel pump that works and doesn't break!

#### DPL70 - 2MFC 2"

Diesel America West's heavy service, self-priming, centrifugal chemical pumps feature quality usually found in heavier and more expensive units. As superstars in the pump world, these pumps are assembled using the finest components available. The Yanmar "W" series diesel, a popular and proven lightweight 4-cycle air cooled engine, is coupled to the super tough fuel rated pump.

Together these units combine to make a serious high performance diesel powered chemical pump that provides the user with easy starting, reliable service, excellent fuel economy, with engine and pump life many times greater than gasoline powered units!

## FNGINF:

- Yanmar L70 W Series Air Cooled 4 Cycle Engine with EPA Cert
- Single Cylinder, Direct Injected, Naturally Aspirated System
- Internally Balanced, Single Counter Rotating Balancer Shaft
- Unit Mounted Air Filter,
   Enclosed Paper Element
   Type
- Engine Mounted Fuel Tank,
   3.06 Quart Capacity
- Automatic Bleeding Fuel System

- Pressure and Splash
   Lubrication, Oil Capacity is
   1.16 Quarts
- Recoil Starting with Auto Decompression System
- Engine Mounted Expansion
   Silencer With Heat Shield
- Rotatable Exhaust Deflector
- Variable Speed Throttle & Governor

#### PUMP:

- 225 G.P.M. Maximum- 62.
   P.S.I. Shut Off Max- 145 Ft.
   TD/Head
- High Performance 2"
   Suction / 2" Discharge NPT

- Ductile Iron Housing and Cast Iron Impeller for Durability
- Aluminum Wear Plate-Non-Sparking
- H / Duty Viton & Silicon Carbide Main Seal - Fuel Compatible
- All Rubber Parts Made of Non-Dissolving Viton
- Built -In Check Valves

## **DIMENSIONS:**

- 22" L x 18" W x 20" H
- Total Weight Complete
   With Frame- 170 Lbs

CALL 1(800)DIESEL-1 FOR A QUOTE